


System 1810D Robot-Matic Selector

SPECIFICATIONS


- ◆ Automatic directional selectivity.
- ◆ LCD backlit display, $\frac{3}{8}$ " x 8" character for descriptive status/error/calibration message.
- ◆ Sealed membrane keypad.
- ◆ RS-232 port for optional computer interface.
- ◆ Capacity to 9999 positions.
- ◆ Audible alarm for key press feedback and error annunciation, visible diagnostics.
- ◆ Interconnecting cables are plug in and are furnished as part of the system.
- ◆ System operates with low power N.E.C., Class 2 current limiting transformer which is part of the conveyor control system. External supply connection is not required.
- ◆ Command unit if housed in a rugged ABS enclosure $4\frac{1}{2}$ " x $7\frac{5}{8}$ " x 2.0".
- ◆ Operation is instantaneous.
- ◆ Not affected by power loss.
- ◆ User-friendly setup procedure.
- ◆ Continuously re-checks settings.




MOUNTING OPTIONS



1. On Counter Surface



2. Below Counter



3. Conveyor Mounting Arm

RAILEX[®] Corp.

89-02 Atlantic Avenue, Ozone Park, NY 11416
Tel: (718) 845-5454 • Fax: (718) 738-1020
www.railexcorp.com ~ railex@railexcorp.com